



ROCKWATER
CONSTRUCTION EQUIPMENT

Address : 1191 N. Patt St., Anaheim, CA 92801 www.rockwaterce.com
Phone : (714) 879-5919 Fax : (714) 879-9149 E-mail : sales@rockwaterce.com
sales@cbhammers.com

For sales and service, contact your Rockwater/ CB Dealer:



READY FOR
ANYTHING



CB Models and Specification

- One of the most powerful and lightest among breakers in the same class.
- Requires less oil flow than other breakers, making it highly efficient.
- Simple construction of the breaker with minimal number of parts enables easy and low-cost maintenance.
- Extremely reliable and durable.
- Works with a wide range of operating pressure and oil flow.
- Auto Lube Kit available as an option.



Compact

- ▶ Size range from CB100 to CB430.
- ▶ Pin-mounted cap with durable and light weight side brackets.
- ▶ Skid Steer mounting caps available for CB300-CB400.
- ▶ Greater productivity with high blow speed.
- ▶ Extremely durable and maintains high reliability.



Medium

- ▶ Size range from CB500 to CB800S.
- ▶ Pin-mounted cap with side plates and enclosed bracket for certain models.
- ▶ Enclosed bracket with damping materials reduces noise level and vibration transmitted to the carrier.
- ▶ High productivity and power is proven.
- ▶ Extremely durable and maintains high reliability.



Heavy

- ▶ Size range from CB1000S to CB1500S.
- ▶ Pin-mounted cap with enclosed bracket.
- ▶ Maximum productivity with heavier blows.
- ▶ Enclosed bracket and its materials provide less noise and minimize shock to the carrier.
- ▶ Extremely durable and reliable.



Optional Auto Lube Kit



Model		CB100	CB200	CB300	CB350	CB400 (390)	CB430
Impact Energy Class	ft. lb	150	210	500	600	800	1,000
Blow Speed	bpm	800 - 1,400	700 - 1,200	600 - 1,100	500 - 900	500 - 900	400 - 800
Oil Supply	gpm	6-11	8-14	10-16	14-20	15-22	18-25
Operating Pressure	psi	1,280 - 1,710	1,280 - 1,710	1,280 - 1,710	1,420 - 1,850	1,560 - 2,000	1,700 - 2,140
Operating Weight	lb (kg)	158 (72)	202 (92)	330 (150)	550 (250)	605 (275)	830 (376)
Overall Length	inch	44.68	49.68	53	47.24	63	73.23
Tool Diameter	inch (mm)	1.6 (40)	1.8 (45)	2.1 (53)	2.4 (60)	2.7 (68)	3.0 (75)
Hose Diameter	inch (mm)	Ø1/2 (12)	Ø1/2 (12)	Ø1/2 (12)	Ø1/2 (12)	Ø1/2 (12)	Ø1/2 (12)
Applicable Carrier	lb (ton)	1,700 - 5,600 (0.8 - 2.5)	2,600 - 6,700 (1.2 - 3.0)	5,500 - 10,000 (2.5 - 4.5)	6,600 - 13,000 (3 - 5.5)	8,800 - 16,000 (4 - 7)	13,000 - 20,000 (6 - 9)

※ Specification and features are subject to change without prior notice for improvement in quality.



CB450	CB500	CB600S	CB700S	CB800S	CB1000S	CB1200S	CB1300S	CB1500S
1,200	2,500	3,500	4,800	5,000	6,000	7,500	9,000	12,000
400 - 800	350 - 700	350 - 650	350 - 600	350 - 500	300 - 450	300 - 450	250 - 400	200 - 350
20-30	30-40	30-45	45-60	50-65	60-75	65-85	70-90	80-105
1,840 - 2,280	2,130 - 2,420	2,130 - 2,420	2,270 - 2,570	2,270 - 2,570	2,270 - 2,570	2,270 - 2,570	2,270 - 2,570	2,270 - 2,570
1,100 (500)	1,750 (795)	2,859 (1,297)	3,307 (1,500)	3,893 (1,766)	4,566 (2,071)	5,803 (2,632)	6,246 (2,833)	8,799 (3,991)
82.72	91.57	102.52	105.94	111.34	120.28	128.15	133.66	146.02
3.3 (85)	3.9 (100)	4.9 (125)	5.3 (135)	5.5 (140)	5.9 (150)	6.1 (155)	6.1 (155)	6.9 (175)
Ø3/4 (19)	Ø3/4 (19)	Ø1 (25)	Ø1 (25)	Ø1 (25)	Ø1 (25)	Ø1 1/4 (32)	Ø1 1/4 (32)	Ø1 1/4 (32)
15,000 - 31,000 (7 - 14)	24,000 - 36,000 (11 - 16)	33,000 - 40,000 (15 - 18)	35,000 - 47,000 (16 - 21)	39,000 - 58,000 (18 - 26)	55,000 - 67,000 (25 - 30)	61,000 - 78,000 (28 - 35)	66,000 - 99,000 (30 - 45)	88,000 - 122,200 (40 - 55)

※ Specification and features are subject to change without prior notice for improvement in quality.

